

Industrial Diesel Engines C2.2

Power Rating

| | |
|----------------|-------------------|
| Maximum Power | 55 kW |
| Maximum Torque | 270 Nm @ 1600 rpm |
| Rated Speed | 2800 rpm |
| Minimum Power | 45 kW |

Emission Standards

| | |
|-----------|--|
| Emissions | U.S. EPA & CARB Tier 4 Final, EU Stage V |
|-----------|--|

General

| | |
|----------------------------|---|
| Engine Configuration | In-Line 4, 4-Stroke-Cycle Diesel |
| Bore | 84 mm |
| Stroke | 100 mm |
| Displacement | 2.2 l |
| Compression Ratio | 17.0:1 |
| Aspiration | Turbocharged (T) or Turbocharged-Aftercooled (TA) |
| Combustion System | Direct Injection |
| Rotation from Flywheel End | Counterclockwise |
| Aftertreatment | DOC+DPF |

Engine Dimensions - Approximate

| | |
|--|--------|
| Length | 807 mm |
| Width | 529 mm |
| Height | 766 mm |
| Weight - Net Dry - Basic Operating Engine Without Optional Attachments | 231 kg |

Aftertreatment Dimensions

| | |
|--------|--------|
| Length | 408 mm |
| Weight | 5.8 kg |

Aftertreatment Dimensions*

| | |
|----------|--------|
| Diameter | 155 mm |
|----------|--------|